




HOPETREK

# LB5 Series Low-Voltage Battery

ESS-LB5/10/15/20



## Key Features:





- Stability & Reliability  
Secured by self-developed cells, modules and BMS
- Independent Physical Protection  
Dual active protection mechanism enhances safety significantly
- Top Safety Certifications for System Security  
IEC62619 IEC62477
- Modular Design.expandable from 5.12-20.48kWh  
Wide capacity range meeting the demand of various scenarios  
Improving your resilience
- Smaller footprint and indoor / outdoor compatible to save your valuable space

[www.hopetrekpower.com](http://www.hopetrekpower.com)

Email: [Marketing@hopetrekpower.com](mailto:Marketing@hopetrekpower.com)

Disclaimer: All rights reserved, including final interpretation and content amendment.

# Specifications

Datasheet	ESS-LB5	ESS-LB10	ESS-LB15	ESS-LB20
System Demo				
Battery Module	LB5 (5.12kWh, 51.2V, 50kg)			
Number of Modules	1	2	3	4
Energy Capacity	5.12kWh	10.24kWh	15.60kWh	20.48kWh
Usable Capacity	4.61 KWh	9.22kWh	14.04kWh	18.43KWh
Dimension (W/D/H)	720/160/656mm	720/160/ 1095mm	720/160/1625mm	720/160/2155mm
Weight	55kg	105kg	155kg	205kg
Standard Charge/ Discharge Current	50A	100A	120A	120A

## General

Battery Type	Cobalt Free Lithium Iron Phosphate (LFP)
Nominal Voltage	51.2V
Operating voltage Range	47.2 - 56.8V
IP Protection	IP65
Installation	Wall-mounted or Floor installation* <sup>1</sup>
Operation Temperature	-10~ 50°C* <sup>2</sup>

## Features

BMS Monitoring Parameters	SOC, System voltage, current, cell voltage, cell temperature, PCBA temperature measurement
Communication Port	CAN
Warranty: 10 years	Yes/optional

## Certification

IEC62619 (Cell&Pack), CE, CEC, RCM, UN38.3

[www.hopetrekpower.com](http://www.hopetrekpower.com)

Email: [Marketing@hopetrekpower.com](mailto:Marketing@hopetrekpower.com)

Disclaimer: All rights reserved, including final interpretation and content amendment.

